

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

ABSTRACT OF THE DISCLOSURE

Methods and apparatus are provided for reducing clipping noise from an OFDM signal, the methods and apparatus are operable to carry out actions including: (a) transforming a received orthogonal frequency division multiplexed (OFDM) signal from a transmission channel into the frequency domain, the OFDM signal having been subject to a clipping function prior to transmission in order to reduce the peak-to-average power ratio (PAPR); (b) recovering data symbols from the transformed OFDM signal, which include clipping noise; (c) estimating the clipping noise in the frequency domain based on the data symbols; and (d) subtracting the estimated clipping noise from the transformed OFDM signal.

NJIT/436-7